



Prezzo di vendita 359,00 €

359,00 €

radio microfono nuovo

## Descrizione

Sistema UHF PLL con true diversity di 3° generazione, con funzione Remoset per il sincronismo.

36Mhz Banda 690-726Mhz

Composto da:

RU-901G3 ricevitore  
RU-G3TH trasmettitore a gelato

### CARATTERISTICHE RICEVITORE RU-901G3

Frequency Preparation

PLL Synthesized Control  
Carrier Frequency Range UHF 470~960 MHz  
Frequency Setting Remoset U Ultrasonic  
Receiving Mode True Diversity  
Bandwidth 36MHz  
S/N Ratio > 105dB  
T.H.D <0.6% @ 1KHz  
Sensitivity -95dBm, S/N>80dB  
CMRR >80 dB  
Audio Frequency Response 50Hz~18KHz±2dB  
Antenna BNC (F)  
Antenna Booster Power DC12~15V/100mA  
Display LCD  
Display Contents Group, Channel, Frequency, Battery Status, Antenna A/B, AF Meter(LED BAR), RF Meter (LED BAR)  
Controls Power ON/OFF, Group, Channel, Frequency, Audio Level, Lock-on, Volume, Output Pad, Frequency Scan (ON/OFF)  
Audio Output Level Ref:±22.5KHz [Dev@1KHz Tone](#)?6.3 Phone Jack:-10dBV XLR Jack:-4dBV(Line)?-24dBV(MIC)  
AF Output Impedance 600?  
Squelch Pilot Tone & Noise Mute  
Output Connector Balanced XLR Socket x1 / Unbalanced ?6.3mm PHONE JACK x1  
Power Supply DC12~15V/500mA  
Dimension (m / m) 212.3mm(W)\*38.3mm(H)\* 144mm(D)  
Notes Actual product specifications may vary depending on region.

### CARATTERISTICHE TRASMETTITORE RU-G3TH

Frequency Preparation PLL Synthesized Control  
Carrier Frequency Range UHF 470~960 MHz  
Frequency Setting Remoset U Ultrasonic  
RF Outputs Low/High  
Stability <±10KHz@ Fc  
Frequency Deviation ±48KHz

Spurious Emissions <-50dBc

Display LCD+LED

Controls Power ON/OFF, Mute ON/OFF, Group, Channel, Frequency, GAIN Adjust, Auto Power Off Adjust, Lock-on Mode

Battery UM3, AA x2

Slot-in Charging Yes

Dimensions 50(W) x 253(H) x 35.5(D)

Notes Actual product specifications may vary depending on model and region.