



Prezzo di vendita625,00 €

625,00 €

cassa nuovo

Descrizione

Caratteristiche:

- 12" LF woofer with 2" voice coil
- 1" exit throat HF compression driver with 1" voice coil
- Frequency response from 48Hz to 20 kHz
- Extremely lightweight: only 13.8Kg

Specifiche:

- 2-way, bi-amplified bass reflex design cabinet
- 700W RMS LF, 200W RMS HF, Class D power amplifiers with switch mode power supply
- DSP with 4-EQ presets
- Control panel with: XLR IN and XLR LINK, Volume, EQ presets, HP filter, GND LFT switch
- 2 x M10 suspension points, 35mm (1.3/8") top-hat speaker stand socket, wall bracket mount flange plate
- 90°H x 60°V constant directivity horn
- Stage monitor angling facility with 12°, 40° or 55° taper

Code: 42603

Configuration: 2 vie

Built-in amplifier LF/HF: 700/200 W RMS

Built-in amplifier peak LF/HF: 1400/400 W

Frequency response: 48Hz - 20KHz -6dB

Low Frequency woofer: 12 - 2 coil mm

High Frequency driver: 1 - 1 coil mm

Maximum SPL cont/peak: 125 / 131 dB

Dispersion: 92° x 60° HxV

Input impedance: 22 Kohm

Crossover Frequency: 1.6 KHz

AC Power requirements: 640 VA

Input connector: XLR with loop, Jack 6.3mm

Power cord: 5 16,4 m

Net Dimension (WxHxD): 402x644x345 15,8x25,4x13,6 mm

Net Weight: 13.8/30.4 Kg

Transport Dimension (WxHxD): 500x745x440 19,7x29,3x17,3 mm

Transport Weight: 16.5/36.4 Kg

